

| | | Dry Containers | | | Open Top | | Flat Rack | | Reefer Containers | | | |
|---------------------|--|----------------|--------|--------|----------|--------|-----------|--------|-------------------|--------|--------|--------|
| | | 20'GP | 40'GP | 40'HC | 20'OT | 40'OT | 20'FR | 40'FR | 20'RF | 20'RH | 40'RF | 40'RH |
| External Dimensions | Length (mm) | 6,058 | 12,192 | 12,192 | 6,058 | 12,192 | 6,058 | 12,192 | 6,058 | 6,058 | 12,192 | 12,192 |
| | Width (mm) | 2,438 | 2,438 | 2,438 | 2,438 | 2,438 | 2,438 | 2,438 | 2,438 | 2,438 | 2,438 | 2,438 |
| | Height (mm) | 2,591 | 2,591 | 2,896 | 2,591 | 2,591 | 2,591 | 2,591 | 2,591 | 2,896 | 2,591 | 2,896 |
| Internal Dimensions | Length (mm) | 5,898 | 12,031 | 12,031 | 5,895 | 12,032 | 5,962 | 12,180 | 5,440 | 5,506 | 11,580 | 11,583 |
| | Width (mm) | 2,352 | 2,352 | 2,352 | 2,350 | 2,352 | 2,350 | 2,230 | 2,300 | 2,304 | 2,280 | 2,280 |
| | Height (mm) | 2,395 | 2,395 | 2,700 | 2,368 | 2,368 | 2,276 | 1,955 | 2,270 | 2,602 | 2,250 | 2,551 |
| Internal Capacity | Cubic Metre | 33.2 | 67.8 | 76.4 | - | - | - | - | 28.4 | 33.0 | 59.5 | 67.3 |
| Door Opening | Height (mm) | 2,280 | 2,280 | 2,585 | 2,280 | 2,280 | - | - | 2,237 | 2,547 | 2,277 | 2,566 |
| | Width (mm) | 2,343 | 2,343 | 2,340 | 2,343 | 2,343 | - | - | 2,300 | 2,300 | 2,280 | 2,280 |
| Ratings | Max Gross WT (kgs) | 30,480 | 30,480 | 30,480 | 30,480 | 30,480 | 34,000 | 45,000 | 27,000 | 27,000 | 30,480 | 30,480 |
| | May Payload (kgs) | 28,335 | 26,830 | 26,680 | 28,080 | 26,640 | 31,000 | 40,050 | 24,070 | 23,675 | 26,492 | 25,480 |
| | *Tare WT (kgs) (include Ref. Unit)* | 2,145 | 3,650 | 3,800 | 2,400 | 3,840 | 3,000 | 4,950 | 2,930 | 3,325 | 3,988 | 5,000 |

This information is provided as a service to Tradewise clients only. All services provided are subject to our standard trading terms and conditions.